

IC 022, IC 022 PLUS

Discover a new dimension in surface cleaning with our revolutionary two - hose dry ice blasting system



Standard dry ice pellets
1.5 mm / 3 mm



Low air consumption
1,1 m³/min



Lightweight
19 kg



Low noise
65 - 85 dB (A)



Added benefit
Maintenance free design

ERGONOMIC BLAST GUN WITH LED LIGHT

2 NOZZLES (ROUND & FLAT)

STANDARD AIR HOSE COUPLING

3 m BLAST HOSE

TROLLEY WITH STORAGE BOX

DRY ICE BOX 25 KG



PRESSURE VALVE ON GUN



EASY - TO - OPERATE



ACCESSORIES




Development



Manufacturing



Maintenance and Repair



Training

Characteristics

Dry ice blasting has never been so affordable! Discover a new dimension of surface cleaning!
Dry ice cleaning is now also available to car workshops, car dealerships, all manufacturing or maintenance companies in any industry, big or small. We bring you a cost-effective alternative to traditional cleaning methods.

The unique design of the IC 022 offers surprising flexibility, performance and power. The maintenance-free feeding system from ICS accepts both 1,5 mm and standard 3 mm dry ice pellets.

The excellent design of the blaster allows easy handling even in tight access spaces. The operation of the machine is easy and fast to get used to.

With IC 022 you are equipped to manage very wide variety of cleaning tasks.

IC 022 with its unique feeding system offers unrivalled performance at an unbeatable price.

Technical specifications

<ul style="list-style-type: none">■ Dimensions Length: 528 mm Width: 296 mm Height: 336 mm	<ul style="list-style-type: none">■ Consumption Dry ice: up to 24 kg/h Compressed air: 1,1 m³/min, depending on the nozzle type	<ul style="list-style-type: none">■ Input Pressure up to 10 bars
<ul style="list-style-type: none">■ Weight Empty machine: 19 kg with the hose	<ul style="list-style-type: none">■ Hopper capacity 4 kg	<ul style="list-style-type: none">■ Operating pressure 8 - 10 bars
<ul style="list-style-type: none">■ Material Casing: Plastic Wheel frame: Stainless steel	<ul style="list-style-type: none">■ Noise level 65 – 85 dB (A) depending on the blasting pressure and the cleaned surface	<ul style="list-style-type: none">■ Compressed air supply: NW 7.2 coupling, acc. ISO 4414/EN 983 standard Minimum requirements for compressed air according to ISO 8573-1:2010 [1:4:1]

IC 022



IC 022 PLUS



Standard package contents

- **10 m Air Hose**
With quick connect fitting
- **Round nozzle**
RN - 20 - 07 - 000
- **Flat Nozzle with Adapter**
FN-20-10-200, NA-20-10-001
- **Protective Equipment Kit**
Protective suit, Gloves, Goggles, Ear plugs, Respirator
- **Dry Ice Shovel**
1 kg Capacity plastic shovel

PLUS Accesories

- **Trolley**
- **Ice Box**




Development



Manufacturing



Maintenance and Repair



Training