

IC 110, IC 110 PLUS

The pneumatically powered dry ice blasting machine with patented feeding system.



Standard dry ice pellets
1.5 mm / 3 mm



Surprising performance
and low consumption



Easy
operation



Low
maintenance



Compact size
Mobile device



EASY OPERATION



PRESSURE CONTROL,
DRY ICE CONSUMPTION CONTROL



FILTERED WATER
SEPARATOR




Development



Manufacturing



Maintenance
and Repair



Training

Characteristics

IC 110 is a medium ICS professional dry ice blasting machine designed for pressures of 10 bar (145 PS) or less which delivers exceptional cleaning performance while maintaining costs of the cleaning process at a minimum level. The pneumatically operated single-hose dry ice blasting machine impresses with the following benefits: very low air consumption, pellet regulation, continuously variable blast pressure regulation, the robust machine is made entirely of stainless steel and distinguishes itself by the excellent manufacture and the powerful design. The design predetermines this machine for businesses' in-house use for tool, machinery or mould maintenance applications.

The machine is characterised by unique compressed air consumption, starting at 1,0 m³/min which makes the unit an unrivalled device in its class.

The ergonomically shaped blasting gun enables blasting even in inaccessible places, it can be supplemented with a Flex Fit ball head, which significantly multiplies the flexibility and availability of the cleaning process. areas of operations and production processes. In combination with the Flex-Case 2 nozzle set, the IC 110 meets even the most demanding user expectations.

IC 110 is a cost effective dry ice blasting solution suitable for variety of applications.

Technical specifications

- | | | |
|---|--|--|
| <ul style="list-style-type: none">■ Dimensions
Length: 500mm
Width: 337 mm
Height: 614 mm | <ul style="list-style-type: none">■ Consumption
Dry ice: max. 60 kg/h
Compressed air: 1.0 – 4.5 m³/min.
depending on the nozzle type | <ul style="list-style-type: none">■ Weight
Empty machine:
39 kg |
| <ul style="list-style-type: none">■ Operating pressure
max 10 bar | <ul style="list-style-type: none">■ Hopper capacity
10 kg | <ul style="list-style-type: none">■ Material
Casing: stainless steel |
| <ul style="list-style-type: none">■ Service supply connections:
Compressed air : DIN 3489 claw coupling | <ul style="list-style-type: none">■ Noise level
60 – 120 dB (A) depending on the blasting
pressure, nozzle type and the cleaned surface | |

IC 110



Standard package contents

- | | | |
|---|--|---------------------------------|
| ■ Plastic nozzle RN-10-06
Round nozzle suitable for
a wide range of uses | ■ Ergonomic Blast gun
With safety switch | ■ Blast hose
5 m 1/2" |
|---|--|---------------------------------|




Development



Manufacturing



Maintenance
and Repair



Training